

**F210 Genoa Comparisons 11/16/04**  
**I= 28.18 J= 7.87 P= 27.03 E= 9.35**

**For: CDI Flexible Furler 2** (Luff tape required is #6; Sail luff deduction is 13" form pin-to-pin length. Recommend use of webbing at head and tack instead of metal grommets. )

Features	North Sails	Doyle	Waters Sails	Sobstad	Schurr	Cruising Dir.	Pope Sails
Cynthia Out Is. Sails 314 968 3172	773-489-1308	800-943-6953 John Baxter	803-957 5638 Joe	800-577-5888 Peter	850-438-9354 Hunter	888 424 7328 Sben/Dan	
e-mail	Perry.lewis@northsails.	doylemidw@aol.com	joe@waterssails	TMONDO@aol.com	loft@schurrsails.com	dan@direct.northsails.com	doug@popesails.com
Name	Soft NorLam	Quicksilver II	Tri-Radial	XVS Tri-Radial		Base Sail \$466	
Construction	Tri-radial Soft Norlam	Bi-Radial Cut	CAD/Computer Cut	Same	Crosscut	Crosscut (Tri mylar \$682 only for racing).	Crosscut w/telltale windows
Weight	5 oz	5.5	4.1		4.5	6.0	5.6
Material	Dacron /mylar /Dacron 122 sqft	Contender Dacron	Dimension Polyant Laminate	Challenge Pentex Laminate w/Taffeta	Dacron	Dacron	Dacron Dim/Poly. 240CMTO
UV Suncover	Dacron recomm.	Dacron	Yes +255 SPF-UV	Yes	Lt. Weight	W/Dacron UV 5 oz.	w/Dacron UV 4.0 oz
Foam Luff Reef Pad	No RopeLuff +180	Yes Rope Luff	No	Yes	No	Reef Pad/ rope +110	No
Draft Stripes	No	Yes	Yes	Yes	No	Yes(2) + \$40 ea	Yes (3)
Adj. Leech cord	Yes	Yes	Yes	Yes	Yes & Foot	Yes	No